



# XYLENE

**CAS NO. 1330-20-7**

Product Description	Key Features	Application
<ul style="list-style-type: none"> <li>Xylene is a clear liquid and water-insoluble. Xylene is stable under recommended storage conditions.</li> <li>Xylene is highly miscible with other common organic solvent. It can be mixed with alcohols, aldehydes, aromatic and aliphatic hydrocarbons, ethers, glycols, glycol ethers and ketones..</li> </ul>	<ul style="list-style-type: none"> <li>Blush resistant</li> <li>Compatible with most substrates used in electronic parts and enclosures</li> <li>Flammable liquid and vapour</li> <li>Good leveling and gloss</li> <li>Highly miscible with other common organic solvents</li> <li>Medium evaporation rate</li> </ul>	<ul style="list-style-type: none"> <li>manufacture of paints</li> <li>varnishes, lacquers, thinners</li> <li>inks</li> <li>rubber</li> <li>pesticides and herbicides</li> <li>paint strippers</li> </ul>

Properties	Typical Value	Unit	Test Based On
Acidity	No Free Acid	mg NaOH/100 mL	ASTM D 847
Acid Wash Color	No.6 Max	-	ASTM D 848
APHA Color	20 Max	-	ASTM D 5386
Appearance	Clear	-	Visual
C8 Aromatic	Report	%wt	ASTM D 2360
Copper Strip Corrosion	Pass (1a or 1b)	-	ASTM D 849
Density at 15 °C (in Vacuum)	Report	g/mL	ASTM D 4052
Density at 15 °C (in Air)	Report	g/mL	ASTM D 4052
Density at 30 °C (in Air)	Report	g/mL	ASTM D 4052
Ethylbenzene	Report	%wt	ASTM D 2360
Non-Aromatic	4.0 Max	%wt	ASTM D 2360
S.G. at 15.6/15.6	0.865 – 0.875	-	ASTM D 4052
Total Sulfur	1.0 Max	ppm wt.	ASTM D 5453
Water Content	Report	ppm wt.	ASTM D 1744

Distillation	Specification	Unit	Test Based On
Distillation Range	5.0 Max	°C	ASTM D 850
Dry Point (DP)	143.0 Max	°C	ASTM D 850
Initial Boiling Point (IBP)	135.5 Min	°C	ASTM D 850

## Notes

The test methods specified above, or their equivalent, will be used. Applicable sampling and testing methods are subject to change without notice and are available for review on request. The values indicated in this document may deviate from the test method requirements by the number of significant figures shown. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock.

This product, including the product name, shall not be used or tested in any medical application without the prior written acknowledgement of Union Petrochemical as to the intended use. For detailed Product Stewardship information, please contact Customer Service.

For additional technical, sales and order assistance please contact our sales representative

©2020-2021. Union Petrochemical. The user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. Union Petrochemical does not guarantee the typical (or other non-specification) values. Typical values only represent the values one would expect if the properties were tested in our laboratories with our test methods on the specified date. Some product properties are not frequently measured, and accordingly typical values may not be based upon a statistically relevant number of tests. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no warranty against patent infringement, not any endorsement of any product or process, and we expressly disclaim any contrary implication.